

HYNC series Hydranlic Nut Splitters

Capacity : 5-90 Ton

Bolt Size : M6 - M48

Max Working Pressure : 700bar

- Compact and ergonomic design, easy to use.
- Unique angled head design.
- Single-acting, spring return cylinder.
- Heavy duty chisels can be reground.
- Applications include service trucks, industry, tank cheaning, petrochemical, piping steel contruction, mining...etc.



HYNC Series Hydranlic Nut Splitter Selection Chart

Model	Capacity (Tons)	Nut Size (mm)	Bolt Size (mm)	Oil Capacity (cm ³)	Length (mm)	Width (mm)	Height (mm)	Weight Kg
HYNC-1319	5	10-19	M6-M12	15	170	40	48	1.2
HYNC-1924	10	19-24	M12-M16	20	191	54	62	2.0
HYNC-2432	15	24-32	M16-M22	60	222	64	72	3.0
HYNC-3241	20	32-41	M22-M27	80	224	75	88	4.4
HYNC-4150	35	41-50	M27-M33	155	288	94	105	8.2
HYNC-5060	50	50-60	M33-M39	240	318	106	128	11.8
HYNC-6075	90	60-75	M39-M48	492	393	156	181	34.1

* The hardness of the nut should not exceed HRc-44.