


RRH series Double-Acting Hollow Plunger Cylinder



Capacity:30~150Ton
 Stroke:38~258mm
 Maximum Operating Pressure:700bar



RRH Series Selection Chart

Capacity (Ton)		Stroke (mm)	Model	Min Height (mm)	Outside Diameter (mm)	Effective Area (cm ²)		Oil Capacity (cm ³)		Plunger Diameter (mm)	Hollow Diameter (mm)	Weight (Kg)
Push	Pull					Push	Pull	Push	Pull			
34	23	178	RRH307A	331	115	47.7	32.4	849	576	63	34	21
30	23	258	RRH3010A	431	115	47.7	32.4	1230	836	63	34	27
60	42	89	RRH603A	248	160	84.2	56.2	749	500	95	53	28
60	42	165	RRH606A	324	160	84.2	56.2	1389	927	95	53	35
60	42	257	RRH6010	438	160	84.2	56.2	2164	1444	95	53	45
100	68	38	RRH1001A	166	212	135.2	87.1	513	331	127	79	33
100	68	76	RRH1003A	255	212	135.2	87	1027	661	127	78	61
100	68	153	RRH1006A	343	212	135.2	87	2068	1331	127	78	79
100	68	253	RRH10010A	443	212	135.2	87	3420	2201	127	78	106
150	75	200	RRH1508	349	247	205	106.8	4100	2136	152	78	111