

BANKO

Straight

for straight wheels

m - 3

m - 4

m - 4P



Oil free



Model		Max. free speed r/min	Spindle thread	Recomended / max. dia. straight wheel (80 m/s)	Max. power kW	Weight kg	Lenght mm	Rec. hose dia. mm	Air inlet thread
Straight for straight wheels									
GSB31 S18 SW	Banko M3 Straight	18000	UNC 1/2x55	80/80	2.0	2.2	472	13	1/2
GSB31 S15 SW	Banko M3 Straight	15000	UNC 1/2x55	100/100	1.9	2.2	472	13	1/2
GSB31 S18 SW	Banko M3 Straight	18000	UNC 5/8x55	80/80	2.0	2.2	472	13	1/2
GSB31 S15 SW	Banko M3 Straight	15000	UNC 5/8x55	100/100	1.9	2.2	472	13	1/2
GSB41 S12 SW	Banko M4 Straight	12000	UNC 5/8x55	125/125	3.1	2.9	467	16	1/2
GSB41 S10 SW	Banko M4 Straight	10000	UNC 5/8x55	125/150	3.0	2.9	467	16	1/2
GSB41 S85 SW	Banko M4 Straight	8500	UNC 5/8x55	125/180	2.9	2.9	467	16	1/2
GSB41P S10 SW	Banko M4P Straight	10000	UNC 5/8x55	150/150	3.3	4.2	470	16	1/2
GSB41P S85 SW	Banko M4P Straight	8500	UNC 5/8x55	180/180	3.3	4.2	470	16	1/2
GSB41P S66 SW	Banko M4P Straight	6600	UNC 5/8x55	230/230	3.2	4.2	470	16	1/2

Adapter for straight wheels with size of wheel must be specified in order