

Die



m - 0
m - 1

Oil free

Model	Die	Max. free speed r/min	Collet diametar	Recomended / max. dia.		Max. power kW	Weight kg	Lenght mm	Rec. hose dia. mm	Air inlet thread
				Carbide burr	Mounted point					
GDB01 D25 CE	Banko M0 DIE	25000	6	12/16	20/25	0.75	0.8	215	10	3/8
GDB01 D18 CE	Banko M0 DIE	18000	6	12/16	20/32	0.75	0.8	215	10	3/8

All GDB01 models are equipped with outlet and inlet air hose, inlet air hose is 1 m long with quick coupling conection (other conectors available at request)
Collet size 8 mm available on request

Model	Die	Max. free speed r/min	Collet diametar	Recomended / max. dia.		Max. power kW	Weight kg	Lenght mm	Rec. hose dia. mm	Air inlet thread
				Carbide burr	Mounted point					
GDB11 D25 CE	Banko M1 DIE	25000	6	12/16	25/32	1.4	1.1	234	10	1/2
GDB11 D18 CE	Banko M1 DIE	18000	6	16/16	32/40	1.3	1.1	234	10	1/2
GDB11 D25 CE VD	Banko M1 DIE	25000	6	12/16	25/32	1.4	1.1	234	10	1/2
GDB11 D18 CE VD	Banko M1 DIE	18000	6	16/16	32/40	1.3	1.1	234	10	1/2

VD - vibration dumped machine for smooth grinding without chatters (only carbide burrs)
Collet size 8 mm available on request